

DELPHION

No active trail


[Select all](#)[Stop tracking](#)[RESEARCH](#)[PRODUCTS](#)[INSIDE DELPHION](#)[Log Out](#)[Work Files](#)[Saved Searches](#)[My Account](#)Search: [Quick/Number](#) [Boolean](#) [Advanced](#) [Derwent](#)[Help](#)

The Delphion Integrated View

Get Now: ☒ PDF | [File History](#) | [Other choices](#)Tools: Add to Work File: [Create new Work File](#)☐ AddView: [INPADOC](#) | Jump to: [Top](#) Go to: [Derwent](#)☒ [Email this to a friend](#)**Title: JP10270086A2: NONAQUEOUS ELECTROLYTE SECONDARY BATTERY****Derwent Title:** Non-aqueous lithium secondary battery e.g. for memory back up or clocks - has negative electrode of tin powder and conductive carbon powder, positive electrode of transition metal oxide and non-aqueous lithium-containing electrolyte [[Derwent Record](#)]**Country:** JP Japan
Kind: A (See also: [JP03200025B2](#))**Inventor:** WATANABE SHUNJI;
SAKATA AKIHITO;
ONODERA HIDEHARU;
SAKAI TSUGIO;
TAWARA KENSUKE;
TAKASUGI SHINICHI;**Assignee:** SEIKO INSTR INC
[News, Profiles, Stocks and More about this company](#)**Published / Filed:** 1998-10-09 / 1997-03-26**Application Number:** JP1997000074170**IPC Code:** Advanced: [H01M 4/02](#); [H01M 10/40](#); [H01M 4/40](#); [H01M 4/48](#);
Core: [H01M 10/36](#); more...
IPC-7: [H01M 4/02](#); [H01M 4/04](#); [H01M 4/38](#); [H01M 4/48](#); [H01M 10/40](#);**Priority Number:** 1997-03-26 JP1997000074170**Abstract:** PROBLEM TO BE SOLVED: To improve battery's cycle characteristics and simplify the manufacturing process and facility, by composing the negative electrode of powdery tin, electron conductive carbon powder, and resin binding agent, using oxide of transition metals as positive electrode active material, and using material in which lithium compound is solved in organic solvent as nonaqueous electrolyte.

SOLUTION: The battery is composed of a negative electrode which consists of powdery tin or tin alloy, electron conductive powdery carbon, and resin binding agent, a positive electrode whose active material is metallic oxide containing transition metals as its element, and lithium-ion-conductive nonaqueous electrolyte in which lithium compound is solved or solid-solved in organic solvent or high molecule. Tin powder composing the negative electrode is produced in a grinding or an atomizing method. It is also effective to use material which is produced by reducing tin oxide with electrochemical reaction between tin oxide and lithium or material containing lithium, inside or outside of the battery after assembling.


COPYRIGHT: (C)1998,JPO

[View Image](#)

1 page

INPADOC None Get Now: [Family Legal Status Report](#)
Legal Status:
Designated AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE
Country:
Family: Show 7 known family members

Forward
References: Go to Result Set: Forward references (1)

PDF	Patent	Pub. Date	Inventor	Assignee	Title
	US6706447	2004-03-16	Gao; Yuan	FMC Corporation, Lithium Division	Lithium metal dispersion in secondary battery anodes

Other Abstract
Info:

[DERABS C98-498225](#)



Nominate this for the Gallery...



Copyright © 1997-2006 The Thomson Corporation

[Subscriptions](#) | [Web Seminars](#) | [Privacy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact Us](#) | [Help](#)